

# Technical Data

## CHAIN & DRIVE Fluid

### High Performance EP Chain and Conveyor Lubricant

#### Description

ROCOL® CHAIN & DRIVE Fluid is a high-performance chain and conveyor lubricant designed to effectively penetrate, lubricate and protect against corrosion.

Also available in aerosol form – see CHAIN & DRIVE Spray, as well as CHAINGUARD HI-LOAD Spray which contains MoS<sub>2</sub> for extra heavy-duty applications.

#### Applications / Industries

- Pin Chain
- Roller Chain
- Conveyors
- Heavy Industry
- Escalators
- Travellators
- Automotive
- Agricultural
- Robotics
- Bicycle Chain

#### Approvals / Specifications

- Siemens – IC SI/I/520
- Hyundai / KIA Group – GB220200712110446

#### Features & Benefits

- Wide temperature range of -15°C to +120°C
- Outstanding EP performance with a weld load of 250 kg
- Protects the chain from wear
- Exhibits excellent penetration into the links and pins of the chain
- Tenacious water-resistant film that protects all types of chains in wet or humid environments
- Excellent corrosion protection on chains in hostile environments
- Good adhesion, reducing dripping and fling

#### Directions For Use

ROCOL CHAIN & DRIVE Fluid can be applied by automatic lubricators or manually.

If applied automatically this should be in accordance with the lubricator manufacturer's instructions.

The storage of ROCOL CHAIN & DRIVE Fluid should be dry and between +1°C and +40°C.

The shelf life is 3 years from date of manufacture.

#### Further Information

For pack sizes, part codes and safety data sheets please visit [www.rocol.com](http://www.rocol.com) or get in touch with our customer service team who will be happy to help: [customer.service@rocol.com](mailto:customer.service@rocol.com)

# Technical Data

## CHAIN & DRIVE Fluid

### High Performance EP Chain and Conveyor Lubricant

Property	Test Method	Result
Appearance	Visual	Amber oily liquid
Base Type	N/A	Mineral oil
Base Fluid Viscosity at 40°C	IP 71	131cSt
Base Fluid Viscosity at 100°C	IP 71	15cSt
Viscosity Index	N/A	118
Performance Additives	N/A	EP
4-Ball Weld Load	IP 239 – ASTM D2596	250kg
Mean Hertz Load	IP 239 – ASTM D2596	58.6kg
Temperature Range	N/A	-15°C to +120°C
Pour Point	IP 15	-24°C
Salt spray Corrosion Resistance 35°C	ASTM B-117	No corrosion (24 hours)
Water Spray for 7 days	N/A	1%
Humidity Cabinet Test 1000 hours at 40°C (100% RH)	ASTM D2247	1%

Values quoted above are typical and do not constitute a specification.

Issue 2 Date: 07/20

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740  
 E customer.service@rocol.com www.rocol.com  
 ROCOL House, Swillington, Leeds LS26 8BS

ROCOL® A division of **ITW** Ltd

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.

