

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Trade name or designation of the mixture	ASSEMBLY PASTE FG
Registration number	-
Synonyms	None.
Product code	UDS000304AE
Issue date	16-June-2022
Version number	1.0
Revision date	16-June-2022
1.2. Relevant identified uses of the local set of the loc	he substance or mixture and uses advised against Lubricants
Uses advised against	None known.
1.3. Details of the supplier of the	safety data sheet
Company name	CRC Industries UK Ltd.
Address	Wylds Road
	Castlefield Industrial Estate
	TA6 4DD Bridgwater Somerset
	United Kingdom
Telephone	+44 1278 727200
Fax	+44 1278 425644
E-mail	hse.uk@crcind.com
Website	www.crcind.com
Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1
	9240 Zele
	Belgium
Telephone	+32(0)52/45.60.11
Fax	+32(0)52/45.00.34
E-mail	hse@crcind.com
Website	www.crcind.com
1.4. Emergency telephone	Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
Health hazards Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Environmental hazards Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

	-	-	-	-
Contains:				Hydrocarbons, C7-C9, isoalkanes

Hazard pictograms



Signal word	Danger
Hazard statements	
H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	

Brovention

Prevention	
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapours.
P271	Use only outdoors or in a well-ventilated area.
Response	Not assigned.
Storage	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental label information	None.
2.3. Other hazards	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Mixture

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C7-C9, isoalkanes	10 - 20	- 921-728-3	01-2119471305-42	-	
		2;H225, Skin Irrit. 2;F quatic Chronic 2;H41	Ι 315, STOT SE 3;Η336, As <mark>ι</mark> 1	o. Tox.	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	1 - 5	13463-67-7 236-675-5	01-2119489379-17	022-006-002	10
Classification:	Carc. 2;H3	351			

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 µm.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Inhalation

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.	
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.	
Ingestion	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.	
4.2. Most important symptoms and effects, both acute and delayed	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.	
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.	
SECTION 5: Firefighting m	neasures	
General fire hazards	Extremely flammable aerosol.	
5.1. Extinguishing media		
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.	
5.3. Advice for firefighters		
Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.	

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.
SECTION 7: Handling and	storage
7.1. Precautions for safe handling	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Limite (MELe) E

UK. EH40 Workplace Expos Components	ure Limits (WELs) Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	4 mg/m3	Respirable.
		4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable
		10 mg/m3	Inhalable dust.
Talc (CAS 14807-96-6)	TWA	1 mg/m3	Respirable dust.
titanium dioxide; [in powder	TWA	4 mg/m3	Respirable.
form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)			
		10 mg/m3	Inhalable
Biological limit values	No biological exposure limits noted fo		
Recommended monitoring procedures	Follow standard monitoring procedure	es.	
Derived no effect levels DNELs)	Not available.		
Predicted no effect concentration	ons (PNECs)		
Components	Value	Assessment factor	
	rm containing 1 % or more of particles v	-	10 μm] (CAS 13463-67-7)
Freshwater Sediment (freshwater)	0.184 mg/l 1000 mg/kg	10 100	
Soil	100 mg/kg	10	
STP	100 mg/l	10	
3.2. Exposure controls			
Appropriate engineering controls	Good general ventilation should be us applicable, use process enclosures, lo maintain airborne levels below recom established, maintain airborne levels shower.	ocal exhaust ventilation, or oth mended exposure limits. If exp	er engineering controls to posure limits have not been
ndividual protection measures,	such as personal protective equipme	ent	
General information	Use personal protective equipment as according to the CEN standards and i equipment.	s required. Personal protection	
Eye/face protection	Wear safety glasses with side shields	(or goggles). Use eye protect	ion conforming to EN 166.
Skin protection			
- Hand protection	When handling the product wear cher time of the glove should be longer tha the breakthrough time, gloves should recommended by the glove supplier.	in the total duration of product be changed part-way through	use. If work lasts longer than . Suitable gloves can be
- Other	Wear appropriate chemical resistant of	clothing.	
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type A)		
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.	
Hygiene measures	When using do not smoke. Always ob after handling the material and before clothing and protective equipment to r	eating, drinking, and/or smok	
Environmental exposure controls	Inform appropriate managerial or sup- from ventilation or work process equip requirements of environmental protec modifications to the process equipme levels.	oment should be checked to en tion legislation. Fume scrubbe	nsure they comply with the ers, filters or engineering

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties Appearance

Physical state	Liquid.
Form	Aerosol.
Colour	White.
Odour	Solvent.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	95 °C (203 °F)
Flash point	7.0 °C (44.6 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	0.9 % estimated
Flammability limit - upper (%)	6 % estimated
Vapour pressure	2140 hPa estimated
Vapour density	Not available.
Relative density	0.92 g/cm3 at 20°C
Solubility(ies)	
Solubility (water)	Insoluble in water
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	
Heat of combustion	Not available.
SECTION 10: Stability and	l reactivity

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

General information

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Skin contact	Causes skin irritation.	
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.	
Symptoms	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.	
11.1. Information on toxicological effects		

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
Hydrocarbons, C7-C9, isoalkanes		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 20 mg/l
Oral		
LD50	Rat	> 5000 mg/kg
	ontaining 1 % or more of particles with aerodynamic	diameter ≤ 10 µm] (CAS 13463-67-7)
<u>Acute</u> Dermal		
LD50	Rabbit	10000 mg/kg
Inhalation	T CODA	roood mg/kg
LC50		> 5 mg/l
Oral		e ngr
LD50	Rat	10000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye	Direct contact with eyes may cause temporary irrita	ation.
irritation		
Respiratory sensitisation	Based on available data, the classification criteria a	are not met.
Skin sensitisation	Based on available data, the classification criteria a	are not met.
Germ cell mutagenicity	Based on available data, the classification criteria a	are not met.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged	exposure.
Reproductive toxicity	Based on available data, the classification criteria a	are not met.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria a	are not met.
Aspiration hazard	Not likely, due to the form of the product.	
Mixture versus substance information	Not available.	
SECTION 12: Ecological in	nformation	
12.1. Toxicity	Harmful to aquatic life with long lasting effects.	
Components	Species	Test Results

Components		Species	Test Results
Hydrocarbons, C7-C9, isoalkanes			
Aquatic			
Acute			
Algae	EC50	Algae	29 mg/l, 72 hours
Crustacea	EC50	Daphnia	2.4 mg/l, 48 hours
Fish	LC50	Fish	18.4 mg/l, 96 hours
Chronic			
Crustacea	NOEC	Daphnia	0.17 mg/l, 21 days
titanium dioxide; [in powder form	containing 1 %	or more of particles with aerodynamic dia	meter ≤ 10 μm] (CAS 13463-67-7)
Aquatic			
Acute			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
12.2. Persistence and degradability	No data is a	available on the degradability of any ingred	ients in the mixture.
12.3. Bioaccumulative potentia	I No data ava	ailable.	
Partition coefficient n-octanol/water (log Kow)	Not availab	le.	
Bioconcentration factor (BCF)	Not availab	le.	

12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. GWP: 2

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

ADI	ĸ	
	14.1. UN number	UN1950
	14.2. UN proper shipping	AEROSOLS
	name	
	14.3. Transport hazard class	(es)
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Hazard No. (ADR)	Not available.
	Tunnel restriction code	D
	14.4. Packing group	Not available.
	14.5. Environmental hazards	No
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
RID		
	14.1. UN number	UN1950
	14.2. UN proper shipping	AEROSOLS
	name	
	14.3. Transport hazard class	(es)
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	14.4. Packing group	Not available.
	14.5. Environmental hazards	
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
ADI	N	
	14.1. UN number	UN1950
	14.2. UN proper shipping	AEROSOLS
	name	
	14.3. Transport hazard class	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	14.4. Packing group	Not available.
	14.5. Environmental hazards	
	14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.
	for user	
IAT		
	14.1. UN number	UN1950

14.2. UN proper shipping name	AEROSOLS	
14.3. Transport hazard class	ss(es)	
Class	2.1	
Subsidiary risk	-	
14.4. Packing group	Not available.	
14.5. Environmental hazards	No	
ERG Code	10L	
14.6. Special precautions	Read safety instructions, SDS and emergency procedures before handling.	
for user		
Other information		
Passenger and cargo aircraft	Allowed with restrictions.	
Cargo aircraft only	Allowed with restrictions.	
IMDG		
14.1. UN number	UN1950	
14.2. UN proper shipping	AEROSOLS	
name		
14.3. Transport hazard class	(es)	
Class	2.1	
Subsidiary risk	-	
14.4. Packing group	Not available.	
14.5. Environmental hazards		
Marine pollutant	No	
EmS	F-D, S-U	
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.	
ADN; ADR; IATA; IMDG; RID		



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm] (CAS 13463-67-7)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
	AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany). ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).
	CAS: Chemical Abstract Service.
	Ceiling: Short Term Exposure Limit Ceiling value.
	CEN: European Committee for Standardization. CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification,
	labeling and packaging of substances and mixtures. GWP: Global Warming Potential.
	IATA: International Air Transport Association.
	IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
	IMDG: International Maritime Dangerous Goods.
	MAC: Maximum Allowed Concentration.
	MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG). MARPOL: International Convention for the Prevention of Pollution from Ships.
	PBT: Persistent, bioaccumulative and toxic.
	REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement
	International concernant le transport de marchandises dangereuses par chemin de fer). RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit.
	TLV: Threshold Limit Value.
	TWA: Time Weighted Average.
	VLE: Exposure Limit Value.
	VME: Exposure Average Value. VOC: Volatile organic compounds.
	vPvB: Very persistent and very bioaccumulative.
	STEL: Short-term Exposure Limit.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any H-statements not written out in full under	
Sections 2 to 15	H225 Highly flammable liquid and vapour.
	H304 May be fatal if swallowed and enters airways.
	H315 Causes skin irritation.
	H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer by inhalation.
	H411 Toxic to aquatic life with long lasting effects.
Revision information	None.
Training information	Follow training instructions when handling this material.

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.