

Description

A food grade, non-toxic oil developed for hydraulic systems in the food, drink, pharmaceutical and packaging equipment industries. Also for use in other applications where a clean, non-staining hydraulic oil is required.

Benefits & Features

- Low friction coefficient for excellent lubrication and wear reduction
- Fully synthetic to provide very wide temperature stability and extended service intervals
- Additives reduce foaming for less residue and scum build up

Directions for Use

For use in hydraulic systems where an ISO 46 viscosity grade is specified. Follow manufacturer's instructions and purge the system of the previous oil before re-filling. Does not contain allergens, genetically modified ingredients, nut oil or derivatives.

Technical Data

Category:	H1 – Lubricants with incidental contact
NSF Registration No:	162783
Allergens:	Does not contain allergens, genetically modified ingredients, nut oil or derivatives.
Appearance:	modified ingredients, nut oil or derivatives.
Base Oil:	Polyalphaolefin
Viscosity:	ISO grade 46
Relative Density:	0.85
Flash Point (COC):	>150°C
Solubility:	Insoluble in water
Operating Temperature Range:	-54° to 200°C
Pack Sizes:	5 Ltr (TF7405) 20 Ltr (TF7420) 205 Ltr (TF7499) 1000 Ltr (TF7400)



The content of this data sheet is given in good faith but without warranty.