

Description

Highly effective for the release of seized and rusted components. A clear low-viscosity oil based product used to aid the removal and freeing of seized nuts and bolts, hinges, locks, tools and fittings with a fast penetrating capillary action. Leaves a clear protective film to guard against further corrosion.

Benefits & Features

- Low viscosity for maximum penetration
- Easy to apply and works quickly
- Leaves a protective film against corrosion
- Also suitable for light lubrication duties
- De-watering capability
- Petroleum wax reinforced for persistence

Directions for Use

Shake can well before use. Spray onto part from 15-30cm and allow to penetrate for a few moments.

Technical Data

Appearance:	Virtually clear, low viscosity liquid drying to a thin greasy state
Odour:	Slightly sweet
Contents:	Blend of petroleum distillates, oils and hydrocarbon propellant. No silicones or chlorinated solvents
Flash Point:	38°C
Solubility:	Insoluble in water
Temperature Range:	Designed for use at ambient temperatures
Relative Density:	0.805
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols



Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.