®®M−

Page 1 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

WD-40® MULTI-USE PRODUCT - [Aerosol]

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Corrosion protection Grease

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GR

WD-40 Company Limited 252 Upper Third Street Milton Keynes, MK9 1DZ, United Kingdom

WD-40 Company Limited PO Box 440

GB-Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom

Tel.: +44 (0) 1908 555400 Fax: +44 (0) 1908 266900 E-Mail: Compliance@wd40.co.uk Homepage: www.wd40.co.uk

WD-40 Company Limited Noorderpoort 93E NL- 5916PJ Venlo

Tel.: +31 85 487 46 91

M

Danka Import Export 548 St Joseph High Road SVR 1018 St Venera

Tel.: +356 21233649 Fax: +356 21233501

E-Mail: Danka@maltanet.net

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

M

Medicines & Poisons Info Office - Mater Dei Hospital, Msida MSD 2090, Malta - Tel.: +356 2545 6508 Emergency Ambulance - Tel.: 112

(RL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.: +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)

+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)



Page 2 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

Telephone number of the company in case of emergencies:

+44 20 3807 3798

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

	•	•	,	` ,
Hazard class	Hazard cat	egory	Hazard	statement

Asp. Tox. 1 H304-May be fatal if swallowed and enters airways.

STOT SE 3 H336-May cause drowsiness or dizziness.

Aerosol 1 H222-Extremely flammable aerosol.

Aerosol 1 H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





Danger

H336-May cause drowsiness or dizziness. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P312-Call a POISON CENTRE / doctor if you feel unwell. P331-Do NOT induce vomiting.

P405-Store locked up. P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Without adequate ventilation, formation of explosive mixtures may be possible.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n a

3.2 Mixtures

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	
aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	919-857-5

GB (RL M)-

Page 3 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

CAS	
content %	60-80
Classification according to Regulation (EC) 1272/2008 (CLP), M-	EUH066
factors	Flam. Liq. 3, H226
	STOT SE 3, H336
	Asp. Tox. 1, H304

Carbon dioxide	Substance for which an EU exposure limit value
	applies.
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	204-696-9
CAS	124-38-9
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-	
factors	

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air.

Remove person from danger area.

Respiratory arrest - Artificial respiration apparatus necessary.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Indestion

Rinse the mouth thoroughly with water.

Consult doctor immediately - keep Data Sheet available.

Do not induce vomiting.

Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

Inhalation:

Headaches

Nausea

Dizziness

Irritation of the respiratory tract

Effects/damages the central nervous system

With long-term contact:

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

®®M−

Page 4 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

Diarrhoea

Danger of aspiration.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Foam

CO2

Extinction powder

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Danger of bursting (explosion) when heated

Danger of explosion by prolonged heating.

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

According to size of fire

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.

Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

®®M—

Page 5 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

Do not use on hot surfaces.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

Take measures against electrostatic charging, if appropriate.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Observe special regulations for aerosols!

Observe special storage conditions.

Keep protected from direct sunlight and temperatures over 50°C.

Store in a dry place.

Store cool.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

© Chemical Name	Hydrocarbons, 0	C9-C11, n-alkane	s, isoalkanes, cy	yclics, <2% aromatics	
WEL-TWA: 800 mg/m3		WEL-STEL:			
Monitoring procedures:	-	Draeger - Hydrod	carbons 0,1%/c	(81 03 571)	
	-	Draeger - Hydrod	carbons 2/a (81	03 581)	
	-	Compur - KITA-1	87 S (551 174)		
BMGV:				Other information:	(OEL acc. to RCP-
				method, paragraphs	84-87, EH40)
R Chemical Name	Hydrocarbons, 0	C9-C11, n-alkane	s. isoalkanes. cv	yclics, <2% aromatics	
OELV-8h: 100 ppm (573 mg/m3		OELV-15min:	<u> </u>	, ooo, == /o a. oaoo	
solvent", [White spirit])	., (
Monitoring procedures:	-	Draeger - Hydro	carbons 0,1%/c	(81 03 571)	
-	-	Draeger - Hydrod	carbons 2/a (81	03 581)	
	-	Compur - KITA-1	87 S (551 174)		
BLV:				Other information:	
Chemical Name	Carbon dioxide				
WEL-TWA: 5000 ppm (9150 mg		WEL-STEL:	15000 ppm (27	400 mg/m3) (WEL)	
5000 ppm (9000 mg/m3) (EU)	<i>5</i> , , (, ,	1111111111	(=: (=:	····g·····g/	
Monitoring procedures:	-	Draeger - Carbo	n Dioxide 0,1%/	a (CH 23 501)	1
	-	Draeger - Carbo	n Dioxide 0,5%/	a (CH 31 401)	
	-	Draeger - Carbon	n Dioxide 1%/a	(CH 25 101)	
	-	Draeger - Carbon	n Dioxide 100/a	(81 01 811)	
	-	Draeger - Carbo	n Dioxide 5%/A	(CH 20 301)	
	-	Compur - KITA-1	26 B (549 475)		
	-	Compur - KITA-1	26 SA (549 467	7)	
	-	Compur - KITA-1	26 SB (548 816	6)	
	-	Compur - KITA-1	26 SF (549 491)	
	-	Compur - KITA-1	26 SG (550 210	0)	
	-	Compur - KITA-1			
	-	Compur - KITA-1			
	-	NIOSH 6603 (Ca			
	-	OSHA ID-172 (C	arbon dioxide ir	n workplace atmospher	es) - 1990
BMGV:				Other information:	

®®®.M

Page 6 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.02.2023 / 0011
Replacing version dated / version: 26.09.2022 / 0010
Valid from: 09.02.2023

PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

OELV-15min:	
Draeger - Carbon Dioxide 0,1%/a (CH 23 501)	
	eres) - 1990
, OELV-ST:	
Draeger - Carbon Dioxide 0.1%/2 (CH 23.501)	
Compur - KITA-126 SF (549 491)	
Compur - KITA-126 SG (550 210)	
Compur - KITA-126 SH (549 509)	
	eres) - 1990
WEL-STEL:	
Draeger - Oil Mist 1/a (67 33 031)	'
Other information:	
OELV-15min:	
Draeger - Oil Mist 1/a (67 33 031)	
Draeger - Oil Mist 1/a (67 33 031) Other information:	
Other information: es WEL-STEL: 6 mg/m3 (paraffin wax, fume)	
Other information:	
Other information: es WEL-STEL: 6 mg/m3 (paraffin wax, fume)	
Other information: Ses WEL-STEL: 6 mg/m3 (paraffin wax, fume) Compur - KITA-187 S (551 174)	
Other information: WEL-STEL: 6 mg/m3 (paraffin wax, fume) Compur - KITA-187 S (551 174) Other information: OS OELV-15min: 6 mg/m3 (paraffin wax, fume)	
Other information: WEL-STEL: 6 mg/m3 (paraffin wax, fume) Compur - KITA-187 S (551 174) Other information: OS OELV-15min: 6 mg/m3 (paraffin wax, fume) Compur - KITA-187 S (551 174)	
Other information: WEL-STEL: 6 mg/m3 (paraffin wax, fume) Compur - KITA-187 S (551 174) Other information: OS OELV-15min: 6 mg/m3 (paraffin wax, fume)	
Other information: WEL-STEL: 6 mg/m3 (paraffin wax, fume) Compur - KITA-187 S (551 174) Other information: OS OELV-15min: 6 mg/m3 (paraffin wax, fume) Compur - KITA-187 S (551 174)	
	Draeger - Carbon Dioxide 0,1%/a (CH 23 501) Draeger - Carbon Dioxide 0,5%/a (CH 31 401) Draeger - Carbon Dioxide 10%/a (CH 25 101) Draeger - Carbon Dioxide 100/a (81 01 811) Draeger - Carbon Dioxide 5%/A (CH 20 301) Compur - KITA-126 B (549 475) Compur - KITA-126 SA (549 467) Compur - KITA-126 SB (548 816) Compur - KITA-126 SF (549 491) Compur - KITA-126 SH (549 509) Compur - KITA-126 SH (549 517) NIOSH 6603 (Carbon dioxide) - 1994 OSHA ID-172 (Carbon dioxide in workplace atmosphe Draeger - Carbon Dioxide 10%/a (CH 23 501) Draeger - Carbon Dioxide 10%/a (CH 25 101) Draeger - Carbon Dioxide 10%/a (CH 20 301) Draeger - Carbon Dioxide 10%/a (CH 20 301) Draeger - Carbon Dioxide 10%/a (CH 20 301) Compur - KITA-126 SH (549 475) Compur - KITA-126 SH (549 467) Compur - KITA-126 SH (549 467) Compur - KITA-126 SH (549 491) Compur - KITA-126 SH (549 509) Compur - KI

Hydrocarbons, C9-C11, n-a	alkanes, isoalkanes, cyclics	, <2% aromatics				
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	46	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	



Page 7 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

Consumer	Human - oral	Long term, systemic effects	DNEL	46	mg/kg bw/day
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	77	mg/kg bw/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3

Oil mist, mineral						
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	0,74	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,19	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,97	mg/kg	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	5,58	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,73	mg/m3	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).
- OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |
- OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

BLV = Biological limit value |

- Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.
- (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).
- OELV-8h = Occupational Exposure Limit Value 8 h (8-hour reference period as a time-weighted average) [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24).
- (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |
- OELV-ST = Occupational Exposure Limit Value Short-term (15-minute reference period)
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).
- [8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24),
- [10] = Respirable fraction (S.L.424.24) |

®®M—

Page 8 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.

[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction. (S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24).

(EU13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (EU14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0,4

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A P3 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties



Page 9 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

Partition coefficient n-octanol/water (log value):

9.1 Information on basic physical and chemical properties

Physical state: Aerosol. Active substance: liquid.

Colour: Light brown Odour: Characteristic

<-66 °C (ASTM D 97, Active substance) Melting point/freezing point:

Boiling point or initial boiling point and boiling range: 176 °C (Active substance) Flammability: Does not apply to aerosols.

0,6 Vol-% ((Particulars of main substances contained)) Lower explosion limit: Upper explosion limit: 8,0 Vol-% ((Particulars of main substances contained))

47 °C (Liquid concentrate) Flash point: Auto-ignition temperature: Does not apply to aerosols.

Decomposition temperature: There is no information available on this parameter. pH:

Mixture is non-soluble (in water).

<=20,5 mm2/s (40°C)

Insoluble

Does not apply to mixtures.

9,4 bar (50°C) 7,2 bar (20°C)

Vapour pressure: Density and/or relative density: 0,817 g/ml (Active substance) Does not apply to aerosols. Relative vapour density: Particle characteristics: Does not apply to aerosols.

9.2 Other information

Kinematic viscosity:

Vapour pressure:

Solubility:

Aerosols:

Aerosols:

Explosives: There is no information available on this parameter.

> Enclosed space ignition test (UN RTDG, Manual of Tests and Criteria, Part III, 31.5): <= 300 g/m3 (deflagration density) Enclosed space ignition test (UN RTDG, Manual of Tests and

> > Criteria, Part III, 31.5): <= 300 s/m3 (time equivalent)

Ignition distance test (UN RTDG, Manual of Tests and Criteria, Aerosols:

Part III, 31.4): >= 75 cm

Oxidising liquids:

SECTION 10: Stability and reactivity

No

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

Pressurized container:

protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

WD-40® MULTI-USE PRODU	CT - [Aeroso	ol]				
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.



Page 10 of 16
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 09.02.2023 / 0011
Replacing version dated / version: 26.09.2022 / 0010
Valid from: 09.02.2023

PDF print date: 06.11.2023 WD-40® MULTI-USE PRODUCT - [Aerosol]

Skin corrosion/irritation:		n.d.a.
Serious eye		n.d.a.
damage/irritation:		
Respiratory or skin		n.d.a.
sensitisation:		
Germ cell mutagenicity:		n.d.a.
Carcinogenicity:		n.d.a.
Reproductive toxicity:		n.d.a.
Specific target organ toxicity -		n.d.a.
single exposure (STOT-SE):		
Specific target organ toxicity -		n.d.a.
repeated exposure (STOT-		
RE):		
Aspiration hazard:		n.d.a.
Symptoms:		n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute	
3. 3					Oral Toxicity)	
Acute toxicity, by dermal	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute	
route:			1119,119		Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>18,5	mg/l/4h	Rat	OECD 403 (Acute	
reate toxicity, by initialation.	LDOO	710,0	1119/1/-111	Ital	Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
OKIT COTTOSION/ITHALION.				Rabbit	Dermal	Repeated
					Irritation/Corrosion)	exposure may
					irritation/Corrosion)	cause skin
						dryness or
0				D-l-l-it	OFOD 405 (A	cracking.
Serious eye				Rabbit	OECD 405 (Acute	Not irritant
damage/irritation:					Eye	
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation	Analogous
					Test)	conclusion
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro	Negative,
ů ,					Mammalian Cell Gene	Analogous
					Mutation Test)	conclusion
Germ cell mutagenicity:				Rat	OECD 478 (Genetic	Negative,
,·					Toxicology - Rodent	Analogous
					dominant Lethal Test)	conclusion
Germ cell mutagenicity:					OECD 479 (Genetic	Negative,
com matagornony.					Toxicology - In Vitro	Analogous
					Sister Chromatid	conclusion
					Exchange assay in	Chinese
					Mammalian Cells)	hamster
Reproductive toxicity:					OECD 414 (Prenatal	Negative,
Reproductive toxicity.					Developmental	Analogous
					Toxicity Study)	conclusion
Caroinogonicity:	NOAEC	1100	mg/m3	Mouse	OECD 453	Female
Carcinogenicity:	NOAEC	1100	mg/m3	iviouse		remale
					(Combined Chronic	
					Toxicity/Carcinogenicit	
0	NOAFO	0000		N4	y Studies)	N4-1-
Carcinogenicity:	NOAEC	>= 2200	mg/m3	Mouse	OECD 453	Male
					(Combined Chronic	
					Toxicity/Carcinogenicit	
					y Studies)	



Page 11 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

Reproductive toxicity (Effects on fertility):	NOAEL	>= 3000	mg/kg bw/d	Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Male
Reproductive toxicity (Effects on fertility):	NOAEL	>= 1500	mg/kg bw/d	Rat	OECD 415 (One- Generation Reproduction Toxicity Study)	Female
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Aspiration hazard:						Yes
Symptoms:						unconsciousnes s, headaches, dizziness, discoloration of the skin, vomiting, diarrhoea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3000	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	1444	ppm	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Analogous conclusion

Carbon dioxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Symptoms:						unconsciousnes
						s, blisters by
						skin-contact,
						vomiting,
						frostbite,
						annoyance,
						palpitations,
						itching,
						headaches,
						cramps, ear
						noises,
						dizziness

11.2. Information on other hazards

WD-40® MULTI-USE PRODUCT - [Aerosol]								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Endocrine disrupting						Does not apply		
properties:						to mixtures.		
Other information:						No other		
						relevant		
						information		
						available on		
						adverse effects		
						on health.		

Carbon dioxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting						No
properties:						

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).



Page 12 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 09.02.2023 / 0011
Replacing version dated / version: 26.09.2022 / 0010
Valid from: 09.02.2023

PDF print date: 06.11.2023 WD-40® MULTI-USE PRODUCT - [Aerosol]

WD-40® MULTI-USE P Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and		28d	>20-	%		OECD 310	Not readily but
degradability:			<60			(Ready	inherent
						Biodegradability -	biodegradable.
						CO2 in sealed	
						vessels	
						(Headspace	
						Test))	
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not apply
disrupting properties:							to mixtures.
12.7. Other adverse							No information
effects:							available on
							other adverse
							effects on the
							environment.
Other information:							DOC-
							elimination
							degree(complex
							ing organic
							substance)>=
							80%/28d: n.a.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus	QSAR	
					mykiss		
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchnerie	OEĆD 201	
					lla subcapitata	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchnerie	OECD 201	
, 0					lla subcapitata	(Alga, Growth	
					'	Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis	OECD 201	
, 0					subcapitata	(Alga, Growth	
					•	Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchnerie	OECD 201	
					lla subcapitata	(Alga, Growth	
					·	Inhibition Test)	
12.2. Persistence and		28d	80	%		OECD 301 F	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
12.3. Bioaccumulative			5-6,7			,	High
potential:							
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substanc

· GB (RL M)·

Page 13 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

To	cicity to bacteria:	EL50	48h	0,95	mg/l		QSAR

Carbon dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	35	mg/l	Salmo gairdneri		
12.5. Results of PBT					-		No PBT
and vPvB assessment							substance, No
							vPvB substance
12.7. Other adverse							Greenhouse
effects:							effect
Other information:	Log Kow		0,83				
Global warming			1				
potential (GWP):							

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

15 01 04 metallic packaging

15 01 01 paper and cardboard packaging

Dispose using dual system.

SECTION 14: Transport information

2

General statements

Transport by	road/by rail	(ADR/RID)
--------------	--------------	-----------

14.1. UN number or ID number: 1950

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: Not applicable

Tunnel restriction code: D
Classification code: 5F
LQ: 1 L

Transport category: **Transport by sea (IMDG-code)**

14.1. UN number or ID number: 1950

14.2. UN proper shipping name:

UN 1950 AEROSOLS

14.3. Transport hazard class(es):
14.4. Packing group:
-

14.5. Environmental hazards:Not applicableMarine Pollutant:Not applicableEmS:F-D, S-U

Transport by air (IATA)

14.1. UN number or ID number:

14.2. UN proper shipping name:

UN 1950 Aerosols, flammable

14.3. Transport hazard class(es): 2.1

14.4. Packing group:

14.5. Environmental hazards: Not applicable











Page 14 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be

considered according to storage, handling etc.):

Ι.		,		
	Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
			dangerous substances as	dangerous substances as
			referred to in Article 3(10) for	referred to in Article 3(10) for
			the application of - Lower-tier	the application of - Upper-tier
			requirements	requirements
	P3b	11.1, 11.2	5000 (netto)	50000 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

65.5 %

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

EUF0002

Revised sections:

1-16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used		
(EC) No. 1272/2008 (CLP)			
Asp. Tox. 1, H304	Classification according to calculation procedure.		
STOT SE 3, H336	Classification according to calculation procedure.		
Aerosol 1, H222	Classification according to calculation procedure.		
Aerosol 1, H229	Classification based on the form or physical state.		

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents. H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard

®®M—

Page 15 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aerosol — Aerosols

Flam. Liq. — Flammable liquid

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

®®M−

Page 16 of 16

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.02.2023 / 0011

Replacing version dated / version: 26.09.2022 / 0010

Valid from: 09.02.2023 PDF print date: 06.11.2023

WD-40® MULTI-USE PRODUCT - [Aerosol]

IUCLIDInternational Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available

NIOSHNational Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.