



TLGU 10

# SKF Ultrasound Lubrication Checker

Ultrasonic sensor improves maintenance practices when re-lubricating bearings

Designed for maintenance technicians, the TLGU 10 uses ultrasonic technology to improve manual re-lubrication. When connected to a grease gun, the intuitive device helps a technician to dispense the correct amount of lubricant into a bearing. By overcoming the problems associated with over- or under-lubrication, it can help to extend bearing life. The device is recommended for a range of bearing applications including electric motors, pumps, fans, compressors and conveyors.

- Easy to use**  
 The TLGU 10 is supplied as a kit. Combining sound with visual displays helps the technician to re-lubricate with maximum accuracy.
- Saves cost**  
 As well as avoiding over-lubrication – and excess grease costs – the added accuracy improves the reliability of a customer’s assets.
- Increases reliability and accuracy**  
 Rather than using theoretical models or experience, a technician is given accurate, real-time guidance on the progress of the re-lubrication process.
- Extends bearing life**  
 Accurate re-lubrication leads to optimum bearing performance, which reduces the likelihood of wear and failure.





## SKF Ultrasound Lubrication Checker

Re-lubrication is critical to extending the life of bearings yet is often carried out based on experience. The TLGU 10 makes re-lubrication a more practical, condition-based process, by delivering the correct amount of lubricant to a bearing at the right time.

The device is simple to use, and relies on a robust, repeatable ultrasound sensor that is optimised for harsh conditions. The sensor monitors the sound of lubricant filling the bearing. Once connected to a grease gun, the

TLGU 10 allows a technician to listen to this sound, via headphones. The sound changes abruptly at the point where the correct amount of lubrication has been applied. In addition, a coloured display indicates noise levels for ease of use.

The combination of sound and visual display helps technicians to re-lubricate quickly and accurately – with the right amount. Under-lubrication can cause premature bearing failure or allow contaminants into the bearing. Over-

lubrication is wasteful and expensive and can cause serious complications. Both over- and under-lubrication can reduce bearing lifetime.

The TLGU 10 helps technicians to deliver the optimum amount of lubricant in order to maximise bearing performance and lifetime.

*Note: The grease gun is not included in the scope of delivery of TLGU 10. SKF offers a range of grease guns which can be purchased separately.*

### Technical data

Designation	TLGU 10		
<b>General</b>		<b>Power</b>	
Description	Ultrasound lubrication detector	Battery	2 AA batteries
Measurement channel	1 channel via a 7 pole LEMO connector	Battery life	7 hours
Display	160x128 pixels Color OLED	Environmental	
Keyboard	5 function keys	Operating temperature	From -10 to +50 °C (14 to 122 °F)
Measuring range	-6 to 99.9 dBµV (reference 0 dB = 1 µV)	IP rating	IP42
Resolution	0.1 dB	<b>Mechanical</b>	
Measurement	Bandwidth 35 to 42 kHz	Housing material	ABS
Signal amplification	+30 to +102 by step of 6 dB	Dimensions instrument	158 × 59 × 38,5 mm (6.22 × 2.32 × 1.51 in)
<b>Audio</b>		Flexible rod length	445 mm (17.51 in)
Amplification	5 adjustable positions in steps of 6 dB	Weight instrument	164 g (5.78 lb)
Maximum output	+83 dB SPL with supplied headset	Carrying case dimensions	530 × 110 × 360 mm (20.9 × 4.3 × 14.2 in)
Headset	25 dB NRR Peltor HQ headset	Total weight (incl. case, sensor and 2 AA batteries)	3 kg (6.6 lb)
Headset connector	Stereo jack connector of 6.35 mm (1/4 in)		

[skf.com](http://skf.com) | [skf.com/mapro](http://skf.com/mapro) | [skf.com/lubrication](http://skf.com/lubrication)

© SKF is a registered trademark of the SKF Group.

© SKF Group 2020

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 19018 EN · November 2020