SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

GEAR OIL SUPER 150 FG

Registration number

Synonyms None

BDS000826BU **Product code** 25-January-2023 Issue date

1.0 Version number

Revision date 25-January-2023

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricants Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd. Company name

Address Wylds Road

> Castlefield Industrial Estate TA6 4DD Bridgwater Somerset

United Kingdom +44 1278 727200

Telephone Fax +44 1278 425644 hse.uk@crcind.com E-mail Website www.crcind.com

CRC Industries Europe by Company name

Address Touwslagerstraat 1

> 9240 Zele Belgium

+32(0)52/45.60.11 Telephone +32(0)52/45.00.34 Fax E-mail hse@crcind.com Website www.crcind.com

1.4. Emergency telephone

Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification

Classification according to Regulation (EC) No 1272/2008 as amended

Environmental hazards

Hazardous to the aquatic environment,

Category 3

H412 - Harmful to aquatic life with

long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

None. **Hazard pictograms** Signal word None.

long-term aquatic hazard

Hazard statements

Harmful to aquatic life with long lasting effects. H412

Material name: GEAR OIL SUPER 150 FG - Ambersil - europe SDS GREAT BRITAIN

Precautionary statements

Prevention

Avoid release to the environment. P273

Response Not assigned. Not assigned. Storage Disposal Not assigned.

Supplemental label information

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information

| Chemical name | % | CAS-No. / EC No. | REACH Registration No. | Index No. | Notes |
|--|---------------------|--|--|---------------|-------|
| 2,6-ditert-butyl-4-methylphenol | <1 | 128-37-0 204-881-4 | 01-2119565113-46 | - | # |
| Classification: | Aquatic A | cute 1;H400, Aquatic | Chronic 1;H410 | | |
| Glycine, N-methyl-N-(1-oxo-9-octadecenyl)-, (Z)- | <1 | 110-25-8 203-749-3 | - | - | |
| | Acute Tox 1;H400 | . 4;H332, Skin Irrit. 2; | H315, Eye Dam. 1;H318, Aq | uatic Acute | |
| Tridecylamine, branched and linear | <1 | 86089-17-0 289-185-9 | - | - | |
| | | a. 4;H302, Skin Corr. 1 quatic Chronic 1;H410 | B;H314, Eye Dam. 1;H318, <i>i</i>) | Aquatic Acute | |

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance. PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16. **Composition comments**

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Exposure may cause temporary irritation, redness, or discomfort.

Treat symptomatically.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

Material name: GEAR OIL SUPER 150 FG - Ambersil - europe

SDS GREAT BRITAIN

BDS000826BU Version #: 1.0 Revision date: 25-January-2023 Issue date: 25-January-2023

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting

procedures

Move containers from fire area if you can do so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Wear appropriate personal protective equipment.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the

SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

The product is immiscible with water and will spread on the water surface. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe

handling

Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

 Components
 Type
 Value

 2,6-ditert-butyl-4-methylphe
 TWA
 10 mg/m3

nol (CAS 128-37-0)

Biological limit values No

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in

discussion with the supplier of the personal protective equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

Material name: GEAR OIL SUPER 150 FG - Ambersil - europe
BDS000826BU Version #: 1.0 Revision date: 25-January-2023 Issue date: 25-January-2023

- Hand protection For accidental contact the use of disposable gloves should be sufficient provided they are changed

immediately after a splash or spill may occur. If intentional contact is expected reusable gloves should be used with a breakthrough time greater than the total duration of the product use. Nitrile

gloves are recommended.

- Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapour cartridge. (Filter type A)

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable

levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Colour Colourless.

Odour Characteristic odor.

Odour thresholdNot available.pHNot applicable.Melting point/freezing pointNot available.Initial boiling point and boilingNot available.

range

Flash point 256.0 °C (492.8 °F)

Evaporation rate Not applicable.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressure

Not available.

Vapour density Not available.

Relative density 0.85 g/cm3 at 20°C

Solubility(ies)

Solubility (water) Insoluble in water

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature > 200 °C (> 392 °F)

Decomposition temperatureNot available.Viscosity150 cSt at 40°CExplosive propertiesNot explosive.Oxidising propertiesNot oxidising.

9.2. Other information

VOC 0 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoidContact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

Material name: GEAR OIL SUPER 150 FG - Ambersil - europe

BDS000826BU Version #: 1.0 Revision date: 25-January-2023 Issue date: 25-January-2023

10.6. Hazardous Not available.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactBased on available data, the classification criteria are not met. **Eye contact**Based on available data, the classification criteria are not met.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components Species Test Results

Glycine, N-methyl-N-(1-oxo-9-octadecenyl)-, (Z)- (CAS 110-25-8)

<u>Acute</u>

Inhalation

LC50 Rat 1.37 mg/l

Oral

LD50 Rat > 2000 mg/kg

Skin corrosion/irritationBased on available data, the classification criteria are not met. **Serious eye damage/eye**Based on available data, the classification criteria are not met.

irritation

Respiratory sensitisationBased on available data, the classification criteria are not met.Skin sensitisationBased on available data, the classification criteria are not met.Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

2,6-ditert-butyl-4-methylphenol (CAS 128-37-0) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityBased on available data, the classification criteria are not met. **Specific target organ toxicity -**Based on available data, the classification criteria are not met.

single exposure

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Mixture versus substance

information

Not available.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects.

Components Species Test Results

Glycine, N-methyl-N-(1-oxo-9-octadecenyl)-, (Z)- (CAS 110-25-8)

Aquatic Acute

Crustacea

EC50 Daphnia 0.68 mg/l, 24 hours

12.2. Persistence andNo data is available on the degradability of any ingredients in the mixture.

degradability

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

2,6-ditert-butyl-4-methylphenol 5.1

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

assessment (EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

Not established.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Material name: GEAR OIL SUPER 150 FG - Ambersil - europe

SDS GREAT BRITAIN

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification,

labeling and packaging of substances and mixtures. GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

VOC: Volatile organic compounds. vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H302 Harmful if swallowed.

Not available.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Revision information

None.

Training information Follow training instructions when handling this material.

Material name: GEAR OIL SUPER 150 FG - Ambersil - europe
BDS000826BU Version #: 1.0 Revision date: 25-January-2023 Issue date: 25-January-2023

Disclaimer

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.