According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY ™ FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : PURITY ™ FG EP GEAR FLUID 100

Product code : PFEP100P20, PFEP100IBC, PFEP100DRX, PFEP100,

PFEP100DRM

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : PURITY FG EP Gear Fluids are food grade extreme pressure

stance/Mixture gear fluids.

NSF H1 Registered.

All components comply with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added

directly to the food product.

1.3 Details of the supplier of the safety data sheet

Manufacturer or supplier's details

Petro-Canada Europe Lubricants Limited

3rd Floor, 1 Ashley Road

Altrincham Cheshire WA14 2DT

United Kingdom

Telephone: +44 (0) 121 781 7264

E-mail address of person responsible for the SDS

: EUSDS@hfsinclair.com

1.4 Emergency telephone number

Emergency telephone num-

: CHEMTREC: +1-703-741-5970;

ber

Poison Control Centre: Consult local telephone directory for

emergency number(s).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. Page: 1 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY [™] FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components			
Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No.		
	Registration number		
alkylated diphenylamine		Repr. 2; H361	0.25 - 1
		Aquatic Chronic 3;	
		H412	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. Page: 2 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY ™ FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Risks : First aider needs to protect himself.

4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

5.2 Special hazards arising from the substance or mixture

fighting

Specific hazards during fire- : Cool closed containers exposed to fire with water spray.

Hazardous combustion prod: :

ucts

Carbon oxides (CO, CO2), silicon oxides (SiOx), smoke and

irritating vapours as products of incomplete combustion.

5.3 Advice for firefighters

Further information Prevent fire extinguishing water from contaminating surface

water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment.

> Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Mark the contaminated area with signs and prevent access to

unauthorized personnel.

Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions Do not allow uncontrolled discharge of product into the envi-

ronment.

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

Page: 3 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY ™ FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation.

Contact the proper local authorities.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Use only with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Advice on protection against :

fire and explosion

None known.

Hygiene measures : Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use. Wash face, hands and any ex-

posed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a dry, cool and well-ventilated place. Keep in properly labelled containers. To maintain product quality, do not store

in heat or direct sunlight.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. Page: 4 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY ™ FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

8.2 Exposure controls

Engineering measures

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protective equipment

Eye/face protection : Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

Filter type : organic vapour filter

Protective measures : Wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : viscous liquid

Colour : Colourless to light yellow.

Odour : Mild petroleum oil like.

Odour Threshold : No data available

Pour point : -39 °C

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. Page: 5 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY [™] FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

Boiling point/boiling range : No data available

Flash point : 264 °C

Method: Cleveland open cup

Fire Point : No data available

Auto-Ignition Temperature : No data available

Evaporation rate : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.8710 kg/l (15 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

No data available

Viscosity

Viscosity, kinematic : 105.0 cSt (40 °C)

12.0 cSt (100 °C)

Flammability : Low fire hazard. This material must be heated before ignition

will occur.

Explosive properties : Do not pressurize, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition.

9.2 Other information

No data available

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. Page: 6 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY [™] FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous polymerisation does not occur. Stable under nor-

mal conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : Reactive with oxidising agents, acids and alkalis.

10.6 Hazardous decomposition products

Hazardous decomposition

products

May release COx, NOx, SOx, methacrylate monomers, formaldehyde, smoke and irritating vapours when heated to de-

composition.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of:

exposure

Eye contact Ingestion Inhalation Skin contact

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : No data available

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY [™] FG EP GEAR FLUID 100

000003000513

Version 4.1 Print Date 05.10.2023 Revision Date 05.10.2023

Serious eye damage/eye irritation

Not classified due to lack of data.

Product:

Remarks No data available

Respiratory or skin sensitisation

Skin sensitisation: Not classified due to lack of data. Respiratory sensitisation: Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Remarks: No data available Toxicity to fish

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

12.2 Persistence and degradability

Product:

Remarks: No data available Biodegradability

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

Page: 8 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY [™] FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

SECTION 14: Transport information

14.1 UN number or ID number

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

IMDG : Not regulated as a dangerous goodIATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

IMDG : Not regulated as a dangerous goodIATA : Not regulated as a dangerous good

14.4 Packing group

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

Page: 9 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY ™ FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

IMDG Not regulated as a dangerous good IATA (Cargo) Not regulated as a dangerous good IATA (Passenger) Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks ADR: Not Regulated

> ADN: Not Regulated RID: Not Regulated

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high : Not applicable

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great Brit-

ain)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

: Not applicable

The components of this product are reported in the following inventories:

DSL On the inventory, or in compliance with the inventory

TSCA All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

IECSC : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

Page: 10 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY [™] FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

SECTION 16: Other information

Full text of H-Statements

H361 : Suspected of damaging fertility or the unborn child. H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Repr. : Reproductive toxicity

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

Order Email for packed goods: pcepackage@hfsinclair.com

Order Email for bulk: pceorders@hfsinclair.com Telephone: +31 88313 0365 / +31 88313 0366 For Product Safety Information: 1 905-491-0565

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license.

Page: 11 / 12 Petro-Canada Lubricants is a HF Sinclair brand

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



PURITY ™ FG EP GEAR FLUID 100

000003000513

Version 4.1 Revision Date 05.10.2023 Print Date 05.10.2023

Prepared by : Product Safety: +1 905-491-0565

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN

Internet: lubricants.petro-canada.com/sds Trademarks are owned or used under license. $Page: 12 \ / \ 12$ Petro-Canada Lubricants is a HF Sinclair brand